

Alloy Machined Side-Eject Tine - .375MT x 4.500L x .320OD







Details

Alloy Machined Side-Eject tines remove a soil core which quickly exits the side of the tine through a precision machined slot. This slot is designed to avoid "plugging" that can occur using hollow tubular tines (especially the smaller diameters) in heavy soil conditions. R&R manufactures a wide selection of these side-eject tines machined from special high-carbon alloy steel solid bar and heat treated to RC45-48 in our own heat treating facility. Very popular for the multiple tine holders which fit all greens aerators.

Replaces

John Deere MT4940, TCU17452 R&R Products RTCU17452

Specifications

Manufacturer
A - Tine Type
Alloy Machined SideEject
B - Tine Mounting
Dia.
C - Tine Length
D - Tine Tip Outside
(Hole) Dia.
E - Tine Tip Inside

R&R Products
Alloy Machined SideEject
375 in (9.5mm)

4.5 in (114mm)
320 in (8.1mm)

(Hole) Dia.
E - Tine Tip Inside
.200 in (5mm)

(Core) Dia.

F - Tine Wall .049 in (1.2mm)

Thickness

Fits Models

John Deere Aercore 1000 John Deere Aercore 1500

TURF Handels GmbH

Am Hartboden 48 Gratkorn, 8101 +43 3124 29064-17

https://turf.rrproducts.com/



RMT4940

Alloy Machined Side-Eject Tine - .375MT x 4.500L x .320OD



John Deere Aercore 2000

John Deere Aercore 800

Toro Greens Aerator

Toro ProCore 1298

Toro ProCore 440

Toro ProCore 648

Toro ProCore 660

Toro ProCore 864

Toro ProCore 880

Toro ProCore 648s