

## Alloy Hollow Tine - .750MT x 6.500L x .570OD





## **Details**

Like Standard Hollow Tines, this tine is also tubular and designed to remove a soil core, but they are constructed from a special high carbon alloy steel. The steel tubing is specially manufactured for R&R to achieve uniform hardness of RC45-48 throughout the tine for excellent wear and toughness. These tines are much tougher and resist bending in extremely hard or rocky soils and you can expect 3-4 times longer life than from the Standard Hollow Tines.

## **Specifications**

Manufacturer R&R Products
A - Tine Type Alloy Hollow
B - Tine Mounting .750 in (19mm)

Dia.

C - Tine Length 6.5 in (165mm) D - Tine Tip Outside .515 in (13.1mm)

(Hole) Dia.

E - Tine Tip Inside .300 in (7.6mm)

(Core) Dia.

F - Tine Wall .072 in (1.8mm)

**Thickness** 

## **Fits Models**

Toro ProCore 1298

Toro ProCore 440

Toro ProCore 648

Toro ProCore 660

Toro ProCore 864

Toro ProCore 880

Toro ProCore 648s

**TURF Handels GmbH** 

Am Hartboden 48 Gratkorn, 8101 +43 3124 29064-17

https://turf.rrproducts.com/