

Alloy Machined Side-Eject Tine with Carbide Tip - .375MT x 4.500L x .400OD R201666





Details

Manufactured from special high-carbon alloy tubular steel with a precision machined slot in the side wall to allow for more efficient core removal in heavy soils. R&R's unique method of machining maintains the maximum side wall height for strength to avoid bending. These tines are through hardened to RC45-48 to create a much tougher and more wear-resistant tine. A carbide tip is then added for even longer life. The advantage of using carbide-tipped tines is the ability to maintain your maximum aerating depth consistently over the life of the tines.

Replaces

R&R Products R108-9114 Toro 108-9114

Specifications

Manufacturer R&R Products
A - Tine Type Alloy Machined SideEject with Carbide Tip
B - Tine Mounting .375 in (9.5mm)

Dia.

C - Tine Length 4.5 in (114mm)
Carbide Tip Carbide Tip
D - Tine Tip Outside .400 in (10.2mm)

(Hole) Dia.

E - Tine Tip Inside

(Core) Dia.

F - Tine Wall .049 in (1.2mm)

.300 in (7.6mm)

Thickness

TURF Handels GmbH

Am Hartboden 48 Gratkorn, 8101 +43 3124 29064-17

https://turf.rrproducts.com/



Alloy Machined Side-Eject Tine with Carbide Tip - .375MT x 4.500L x .4000DR201666



Fits Models

John Deere Aercore 1000

John Deere Aercore 1500

John Deere Aercore 2000

John Deere Aercore 800

Toro Greens Aerator

Toro ProCore 1298

Toro ProCore 440

Toro ProCore 648

Toro ProCore 660

Toro ProCore 864

Toro ProCore 880

Toro ProCore 648s

Am Hartboden 48 Gratkorn, 8101 +43 3124 29064-17

https://turf.rrproducts.com/